



IMPLEMENTS CATALOGUE



- Maximum disc penetration 240 mm
- Lateral and angle draw-bar adjustments for tracking
- Oil bath bearings
- Constant level device



CAESAR HARROW 7'6'

90*90*6

50mm*50mm

20 disc

Standard quadrisection

Solid bar subframe

- Robust, steel fabricated\, durable construction
- Good for achieving depth
- Minimum wearing parts
- Hub and hub cap made from high grade cast steel for minimum wear
- Wide range of adjustments enabling ploughing in the toughest conditions
- Ecient, low maintenance year after year
- Quick and easy conversion from standard plough to trash plough
- 3 way adjustable tail wheel



P11 PLOUGH

3 Discs

Mass 600kg

Hp 65-75

51*61 cm disk spacing

60*110 cm width of cut



- 6 Cubic meter capacity
- 75*38 Channel support frame
- 32mm Rebar tipping hook points
- 40 mm Bright steel lifting lugs
- 50*5mm weld reinforcing ribs
- Long hydraulic beam
- Holes for drainage
- Not prone to rust
- Clearance for picking up with forklift



SKIP BIN

Length 3m

Width 1,8 m

Depth 1,4 m

- No gearbox, minimum maintenance costs
- Blade speed 3350m per minute
- Two free swinging cranked 16mm tempered steel blades.
- Replaceable skid plates
- Reversible rubber tyre
- No damage to other moving parts in the event that blades come in contact with a hard object



ROTARY GEAR BOX MOWER

1,52 M Width of cut

2-4 Blades

P.T.O 540

Mass 500

Hp 35+



- Robust sprung channel iron frame
- Reversible hitch
- Standard Bain Bearings and hubs
- Standard rare tow hitch



6M STEEL DECK TRAILER

Deck M size 4,8M*2M

Payload 5TON

Wheels 750*16

Mass 992

Hp 30

- Robust steel Frame
- Resistant to rust



5000 LTR WATER BOWSER

Capacity 5000l



- Designed to handle everything from weaners to bulls
- Positive action ratchet mechanism for quick control and release with one hand
- Steel tubing constructions for animal safety
- The ratchet lock/release mechanism is set with the correct tolerance



CATTLE BAIL

Top 100cm

Bottom 10 cm

Height 186 cm

Mass 120kg

- Robust frame and tines
- Adjustments for hard ripping
- Good for breaking plough pan
- Good for minimum tillage
- Good for achieving depth
- Good for Virgin land and ripping up of roots and stones
- Attachment options available
- Shatter points available
- Wet or dry ripping adjustments
- Replaceable high carbon cast steel points



VULCAN 2/3 RIPPER

Mass 513 kg

HP 75-80

2 Tynes



- Robust frame and tines
- Added swath
- Adjustments for hard ripping
- Good for breaking plough pan
- Good for minimum tillage
- Good for achieving depth
- Good for Virgin land and ripping up of roots and stones
- Attachment options available
- Shatter points available
- Wet or dry ripping adjustments
- Replaceable high carbon cast steel points



VULCAN 3/5 RIPPER

Mass 596 kg

HP 80-90

3 Tynes





Bain New Holland

35 Douglas Road, Workington, Harare, Zimbabwe

Tel: 263-242-621081-5/6/7

bain@bain.co.zw | www.bain.co.zw