

**TT**

TT55 | TT65 | TT75



SPECIFICATIONS

| Models   | TT.55                         | TT.65            | TT.75             |
|--|-------------------------------|------------------|-------------------|
| <b>Engine</b>  | New Holland S8000             |                  |                   |
| No. of Cylinders / aspiration  | 3 / Turbo charge              | 3 / Turbo charge | 4 / Turbo charge  |
| Capacity (cm <sup>3</sup> )  | 2931                          | 2931             | 3908              |
| Bore x stroke (mm)   | 104 x 115                     | 104 x 115        | 104 x 115         |
| Power @ rated speed (2500rpm) (kW/hp(CV))  | 40.25/54                      | 48/64.4          | 54.7/73.4         |
| Max. torque (gross) (Nm@rpm)   | 210 @ 1400                    | 260 @ 1400       | 290 @ 1400        |
| Torque rise (%)  | 22                            | 35               | 41                |
| Fuel tank capacity (l)   | 63                            | 63               | 63                |
| Transmission - 30 kph  | 8F + 2R partially synchromesh |                  |                   |
| Speed range (kph)  | 2.66 - 25.49                  | 2.87 - 29.97     | 3.28 - 31.85      |
| Optional with creeper (F+R)  | 12 + 3                        | 12 + 3           | 12 + 3 (standard) |
| Min. speed with creeper (kph)  | 0.86                          | 0.93             | 1.06              |
| Optional without creeper (F+R)   | 12 + 3                        | 12 + 3           | 12 + 3            |
| Speed range (kph)  | 2.00 - 29.74                  | 1.93 - 29.97     | 2.21 - 31.85      |
| <b>Rops and Canopy</b>   | <b>Standard</b>               |                  |                   |
| <b>Axle</b>  |                               |                  |                   |
| 2WD front axle   | ●                             | ●                | ●                 |
| 4WD front axle   | ●                             | ●                | ●                 |
| <b>Hydraulics</b>  |                               |                  |                   |
| Top link draft sensing   | ●                             | ●                | ●                 |
| Rear linkage category  | Cat. II                       | Cat. II          | Cat. II           |
| Mechanical lift with Lift-O-Matic™   | ●                             | ●                | ●                 |
| Position, draft, mixed and float controls  | ●                             | ●                | ●                 |
| Main pump flow - Standard (lpm)  | 34                            | 34               | 34                |
| Steering pump flow (lpm)   | 26                            | 26               | 26                |
| Max. number of remote valves   | 2                             | 2                | 2                 |
| <b>Linkage</b>   |                               |                  |                   |
| Max. lift capacity at ball ends with no assist arms (kg)                                     | 1400                          | 1480             | 1480              |
| Max. lift capacity at ball ends with assist arms (kg)  | n/a                           | 2000             | 2000              |
| <b>PTO</b>   |                               |                  |                   |
| Engine speed at:   |                               |                  |                   |
| 540 rpm (rpm)  | 1967                          | 1967             | 1967              |
| PTO activation   | mechanical                    | mechanical       | mechanical        |
| <b>Steering</b>  |                               |                  |                   |
| Turn angle 2WD/4WD (°)   | 52/38                         | 52/38            | 52/38             |
| Min. turn radius 2WD/4WD (mm)  | 3205/4200                     | 3200/4200        | 3275/4200         |
| <b>Weights</b>   |                               |                  |                   |
| Minimum weight ROPS 2WD/4WD with front carrier & no additional ballast provided on rear (kg) | 2275/2330                     | 2605/2400        | 2840/2800         |
| Standard weight (kg)   | 2505/2560                     | 2895/2690        | 3180/3200         |
| <b>Dimensions</b>  |                               |                  |                   |
| <b>A</b> Overall length 2WD/4WD (mm)   | 3490/3710                     | 3515/3790        | 3570/3810         |
| <b>B</b> Overall width 2WD/4WD (mm)  | 1930/1930                     | 2025/2025        | 1990/1990         |
| <b>C</b> Height to top of exhaust 2WD/4WD (mm)   | 2200/2210                     | 2247/2425        | 2425/2425         |
| <b>D</b> Wheelbase 2WD/4WD (mm)  | 2055/2010                     | 2090/2050        | 2205/2160         |
| <b>E</b> Track width   |                               |                  |                   |
| Front standard 2WD/4WD (mm)  | 1400/1445                     | 1410/1545        | 1410/1545         |
| Rear standard 2WD/4WD (mm)   | 1470/1475                     | 1570/1520        | 1510/1520         |
| <b>F</b> Ground clearance under rear axle (mm)   | 475                           | 500              | 500               |

● Standard



Visit our website: [www.newholland.com/za](http://www.newholland.com/za)



The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by CNHI INTERNATIONAL SA. Brand Marketing and Communication. creative-farm.it - 04/19 - RSA19103